

# ULTRA-GUARD FLASHPRENE UN

7 FLUID APPLIED | Flexible Flashing Accessory



## GENERAL DESCRIPTION

Ultra-Guard Flashprene UN is a thermoset flashing material made of uncured neoprene rubber.

## BASIC USE

Ultra-Guard Flashprene UN is typically used as the heavy-duty reinforcing and exposed flashing membrane in conjunction with GMX's Ultra-Guard HA 551 rubberized waterproofing membrane. Ultra-Guard Flashprene UN's unique properties provide ease in forming around penetrations and corners as well as detailing expansion / control joints and drains.

## SIZES

The Ultra-Guard Flashprene UN membrane is available in a standard thickness of 60 mils (0.060 inch), standard widths of 12, and 18 inches, and a length of 100.5 feet.

## TECHNICAL DATA | PRODUCT SPECIFICATIONS

Type: Ultra-Guard Flashprene UN

<b>Thickness, Inches</b> ASTM D751	.060 + 10%
<b>Width, inches</b> ASTM D751	12, 18 inches
<b>Length, Feet</b> ASTM D751	100 + .5 foot
<b>Tensile Strength, minimum PSI</b> ASTM D412 Die C	1800
<b>Elongation, Ultimate, minimum %</b> ASTM D412	300
<b>Tear Resistance, minimum, lbf/inch</b> ASTM D624 Die C	175
<b>Brittleness Point Temperature</b> ASTM D746	-40°F
<b>Ozone Resistance 168 hours/ 100 PPHM/104° F. 40°C./50% ext</b> ASTM D1149	No Cracks @ 7X magnification
<b>Resistance to Water Absorption, % increase in weight max after 7 days @ 75° F.</b> ASTM D471	1%

## May help to contribute to LEED® credits:

<b>EA Credit 1:</b>	Optimize Energy Performance
<b>EQ Credit 3.1:</b>	Construction IAQ Management Plan: During Construction
<b>EQ Credit 4.2:</b>	Low Emitting Materials: Paints and Coatings
<b>MR Credit 5.1:</b>	Regional Materials: 10% Extracted, Processed and Manufactured Regionally
<b>MR Credit 5.2:</b>	Regional Materials: 20% Extracted, Processed and Manufactured Regionally

## SHIPPING INFORMATION

<b>Proper Shipping Name:</b>	Non-regulated material Water-based asphalt emulsion
<b>Hazard Class:</b>	Not Applicable
<b>Identification:</b>	Not Applicable
<b>Packaging Group:</b>	Not Applicable

**NOTE:** Applies to DOT-U.S./ MOT-CANADA/INT'L (ALL MODES).

**CAUTION:** Ultra-Guard Flashprene UN is a water-based material. KEEP FROM FREEZING DURING TRANSIT AND STORAGE.



**GMX, Inc.**  
3014 Chamber Dr.  
Monroe, NC 28110  
Toll Free: 866-228-7743  
[www.gmxwaterproofing.com](http://www.gmxwaterproofing.com)

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperatures, application methods, test methods, actual site conditions and curing conditions. Installation conditions and methods can impact product performance. Consult your local GMX Sales Representative for Questions.

PRIOR TO EACH USE OF ANY GMX PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS & INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [WWW.GMXCO.COM](http://WWW.GMXCO.COM) OR BY CALLING GMX AT 866-228-7743. NOTHING CONTAINED IN ANY GMX MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH GMX PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.