

FASTAPE SRA-W

7 & 3 SEAM TAPE



DESCRIPTION

Low Density Polyethylene Film Tape - 9.0 mil - Synthetic Rubber-Based Adhesive remains permanently tacky and bonds well to most surfaces over a wide range of temperatures, providing an excellent low-temperature bond. Tough polyethylene backing offers good abrasion and tear resistance. Highly conformable, waterproof and resistant to chemical deterioration.

APPLICATIONS

FasTape Commercial Tape is ideal for sealing seams in DrainMax applications used for blindside drainage with the TegoBloc Swell Waterproofing System.

FasTape Commercial Tape is also used in applications involving Bilar membrane, for sealing seams and details.

TECHNICAL DATA | PRODUCT SPECIFICATIONS

Type: FasTape Commercial Tape

Property	Value
Total Thickness	9.0 mil (0.229 mm)
Tensile Strength	22 lbs/inch width
Elongation	100%
Adhesion to Steel	60 oz/inch
Adhesion to Backing	35 oz/inch
Moisture Vapor Transmission	0.4 grams/100 sq. in/24 hrs.
Color	White
Format	4" x 180'
Core	3"



GMX, Inc.
3014 Chamber Dr.
Monroe, NC 28110
Toll Free: 866-228-7743
www.gmxco.com

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperatures, application methods, test methods, actual site conditions and curing conditions. Installation conditions and methods can impact product performance. Consult your local GMX Sales Representative for Questions.

PRIOR TO EACH USE OF ANY GMX PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS & INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT WWW.GMXCO.COM OR BY CALLING GMX AT 866-228-7743. NOTHING CONTAINED IN ANY GMX MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH GMX PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.