

**PRODUCT DESCRIPTION**

TegoBase™ is a lightweight non-asphaltic protection board/base sheet with excellent weatherability, which enhances the overall flexibility and fatigue resistance of both hot and cold fluid applied waterproofing systems. TegoBase™ is composed of recycled plastic and binders, reinforced with high strength fiberglass.

- System compatibility
- Ultra-Guard® HA551 System
- Ultra-Guard® Elastomeric HB System
- Excellent flexibility
- Excellent weatherability
- Easy to apply
- Excellent dimensional stability

**Storage and Handling Considerations:** Sheets should be stored under cover away from direct exposure to the elements until immediately before use. If it becomes necessary to store material on the job site or roof deck, units should be covered with an opaque tarpaulin or similar cover. (Clear or black protective coverings are not acceptable.) Units should also be stored elevated from the roof deck by placement on a pallet. If possible, materials should be stored inside away from direct sunlight at the job site. Do not stack units more than two pallets high.

**APPLICATION**

TegoBase™ is embedded directly into the hot Ultra-Guard® HA 551 membrane in horizontal deck applications (or vertically if called for in the design), with sides and ends abutted, as a protection course. When used in a detail, follow those installation instructions. TegoBase is installed with the most current published application instructions for Ultra-Guard® Elastomeric HB system.

**AVAILABILITY AND COST**

GMX materials are produced in and shipped from our Monroe, NC plant. For the name and number of the nearest GMX representative and/or pricing, call us at 866-228-7743.

**HIGH PERFORMANCE DURABILITY**

GMX warrants its material to be free from defects at the time of installation and will offer a commercial warranty for 10 years provided our materials are applied in accordance with the published specifications in effect at the time of installation. For specific warranty terms and conditions, contact your local GMX representative.

**TECHNICAL SERVICES**

Your local GMX representative is available to assist you in selecting the appropriate product and to provide on site application assistance. For further information, please contact our Technical Service Dept. at 866-228-7743.

**TECHNICAL DATA | PRODUCT SPECIFICATIONS**  
Type: TegoBase™

<b>Sheet Dimensions</b>	3 ft. X 4 ft.
<b>Water Absorption</b>	< 3% maximum
<b>Approx. Coverage</b>	12 FT.2
<b>Top Surface</b>	Recycled Plastic Fibers
<b>Bottom Surface</b>	Recycled Plastic Fibers
<b>Nominal Thickness</b>	3.5 mm
<b>Nominal Weight</b>	3.5 LBS
<b>Reinforcement</b>	Fiberglass fibers
<b>Softening Point</b> (ASTM D-36)	N/A
<b>Cold Flexibility</b> (ASTM D-5147)	Pass
<b>Puncture Strength</b> (ASTM D-6505)	365 N (82.1bf.)
<b>Resistance to Decay</b> (ASTM D-6507)	Pass

**May help to contribute to LEED® credits:**

<b>EA Credit 1:</b>	Optimize Energy Performance
<b>EQ Credit 3.1:</b>	Construction IAQ Management Plan: During Construction
<b>EQ Credit 4.2:</b>	Low Emitting Materials: Paints and Coatings
<b>MR Credit 5.1:</b>	Regional Materials: 10% Extracted, Processed and Manufactured Regionally
<b>MR Credit 5.2:</b>	Regional Materials: 20% Extracted, Processed and Manufactured Regionally

**SHIPPING INFORMATION**

<b>Proper Shipping Name:</b>	Non-regulated material
<b>Hazard Class:</b>	Not Applicable
<b>Identification:</b>	Not Applicable
<b>Packaging Group:</b>	Not Applicable

**NOTE:** Applies to DOT-U.S./ MOT-CANADA/INT'L (ALL MODES).



**GMX, Inc.**  
3014 Chamber Dr.  
Monroe, NC 28110  
Toll Free: 866-228-7743  
[www.gmxco.com](http://www.gmxco.com)

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperatures, application methods, test methods, actual site conditions and curing conditions. Installation conditions and methods can impact product performance. Consult your local GMX Sales Representative for Questions.

PRIOR TO EACH USE OF ANY GMX PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS & INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT [WWW.GMXCO.COM](http://WWW.GMXCO.COM) OR BY CALLING GMX AT 866-228-7743. NOTHING CONTAINED IN ANY GMX MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH GMX PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.