

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 05/21/2025 Date of Issue: 08/17/2016 Version: 2.1

SECTION 1: IDENTIFICATION

 Product Identifier

 Product Form: Fluid applied, solvent borne, elastomeric air, vapor and water barrier

 Product Name: Ultra-Shield Below Grade Waterproofing

 Product Number: 1720

 Name, Address, and Telephone of the Responsible Party

 Manufacturer

 GMX, Inc.

 3014 Chamber Dr

 Monroe, NC 28110

 Emergency Telephone Number

 Emergency Number: 1-800-424-9300 (CHEMTREC)

 Main Switch Board: (704) 334-8222

Classification of the Substance or Mixture

Classification (GHS-US) H225 – Flam. Liq. 2 H304 - Asp. Tox. 1 H319 – Eye irrit. 2A H340 - Muta. 1B H350 - Carc. 1B H400 - Aquatic Acute 1 H411 - Aquatic Chronic 2

Label Elements

GHS-US Labeling Hazard Pictograms (GHS-US)



Signal Word (GHS-US) Hazard Statements (GHS-US)		Danger H225 – Highly flammable liquid and vapor. H304 - May be fatal if swallowed and enters airways H319 – Causes serious eye irritation. H340 - May cause genetic defects by route of exposure if conclusively proven that no other route applies. H350 - May cause cancer by route of exposure if conclusively proven that no other
Precautionary Statements (GHS-US)	:	route applies H400 - Very toxic to aquatic life. H411 - Toxic to aquatic life with long lasting effects. P201 – Obtain special instructions before use. P202 – Do not handle until all safety precautions have been read and understood. P210 – Keep away from heat. P233 – Keep container tightly closed.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 05/21/2025 Date of Issue: 08/17/2016 Version: 2.1 P240 – Ground/bond container and

receiving equipment.

P241 – Use explosion-proof electrical/ventilating/equipment.

P242 – Use only non-sparking tools.

P243 – Take precautionary measures against static discharge.

P264 – Wash face, hands, and any exposed skin thoroughly after handling.

P273 - Avoid release to the environment.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P281 – Use personal protective equipment as required.

P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 – If exposed or concerned: Get medical advice/attention.

P337+P313 – if eye irritation persists: Get medical attention/advice.

P370 + P378 - In case of fire: Use extinguishing media for extinction.

P391 - Collect spillage.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P405 – Store locked up.

P501 – Dispose of contents/container according to local, regional, national, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Not available.

Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Substance</u>

Not available

<u>Mixture</u>

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum Asphalt	CAS No (8052-42-4)	60-100	H225 - Flam. Liq. 2
			H319 – Eye Irrit. 2A
			H351 – Carc. 2
Solvent Naphtha, petroleum, light aromatic	CAS No (64742-95-6)	30-60	H226 - Flam. Liq. 3
			H340 - Muta. 1B
			H350 - Carc. 1B
			H304 - Asp. Tox. 1
			H400 - Aquatic Acute 1
			H411 - Aquatic Chronic 2
Poly(butadiene-co-styrene)	CAS No (9003-55-8)	5-10	Not a hazardous substance
SECTION 4: FIRST AID MEASURES			

Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

First-aid Measures After Inhalation: Move to fresh air. Oxygen or artificial respiration if needed. If symptoms persist, call a physician.

First-aid Measures After Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician. **First-aid Measures After Eye Contact**: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

First-aid Measures After Eye Contact: Rinse thoroughly with pienty of water for at least 15 minutes and consult a physician.

First-aid Measures After Ingestion: Call a physician or Poison Control Center immediately. Never give anything by mouth to an

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 05/21/2025 Date of Issue: 08/17/2016 Version: 2.1

unconscious person. Do not induce vomiting without medical advice.

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide (CO2). Foam. Dry powder. Dry chemical.

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

Special Hazards Arising From the Substance or Mixture

No information available

Advice for Firefighters

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Evacuate personnel to safe areas.

For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and Material for Containment and Cleaning Up

For Containment and Clean Up: Dike with inert absorbent material (e.g. dry sand or earth). Take precautionary measures against static discharges. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Keep in suitable and closed containers for disposal. Dispose of as common waste.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Remove and wash contaminated clothing before re-use. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat and sources of ignition. Keep out of the reach of children.

Control Parameters

Chemical Name	ACGIH TLV	OSHA PEL	Ontario TWAEV	Mexico
Petroleum Asphalt	TWA: 0.5 mg/m ³		TWA: 0.5 mg/m ³	STEL: 10 mg/m ³
				TWA: 5 mg/m ³
Stoddard Solvent	TWA: 100 ppm	TWA: 2900 mg/m ³	TWA: 525 mg/m ³	STEL: 200 ppm
		TWA: 500 ppm		STEL: 1050 mg/m ³
				TWA: 523 mg/m ³
				TWA: 100 ppm

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	Revision Date: 05/21/2025	NIOSH IDLH	Version: 2.1
Stoddard Solvent		20000 mg/m ³	

Exposure Controls

Appropriate Engineering Controls: Do not allow ventilation equipment to draw material odors indoors. Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.



on and body redection. wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Hygiene Measures: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

Other Information: When using, do not eat, drink, or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties					
Physical State	:	Liquid			
Appearance	:	Petroleum Distillates			
Odor	:	Slight odor			
Odor Threshold	:	Not available			
рН	:	Not available			
Relative Evaporation Rate (butyl acetate = 1)	:	Not available			
Melting Point	:	Not available			
Freezing Point	:	32°F/ 0°C			
Boiling Point	:	300-390°F / 149-199°C			
Flash Point	:	Not available			
Auto-ignition Temperature	:	540°F / 282°C			
Decomposition Temperature	:	Not available			
Flammability (solid, gas)	:	Not available			
Lower Flammable Limit	:	Not available			
Upper Flammable Limit	:	Not available			
Vapor Pressure	:	6-10 mmHg			
Relative Vapor Density at 68°F (20°C)	:	3.9-4.3 @ Air = 1			
Relative Density	:	Not available			
Specific Gravity	:	0.91			
Solubility	:	slightly soluble			
Partition coefficient: n-octanol/water	:	Not available			
Explosion Data – Sensitivity to Mechanical Impact	:	Not available			
Explosion Data – Sensitivity to Static Discharge	:	Not available			
VOC Content	:	Not available			

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 05/21/2025 Date of Issue: 08/17/2016 Version: 2.1

Reactivity: Hazardous polymerization does not occur

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: No information available.

Incompatible Materials: No materials to be especially mentioned.

Hazardous Decomposition Products: Carbon monoxide. Carbon dioxide. Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects – Ingredient(s)

LD50 and LC50 Data

Asphalt (8052-42-4)	
LD50 Oral Rat	>5,000 mg/kg
LD50 Dermal Rabbit	>2,000 mg/kg

Carcinogenicity Data:

Asphalt (8052-42-4)	
IARC Group	2B
National Toxicity Program (NTP) Status	Twelfth Report – Items under consideration.

SECTION 12: ECOLOGICAL INFORMATION

<u>Toxicity – Ingredients</u>

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Persistence and Degradability

No information available for this product.

Bioaccumulative Potential – Product

No information available for this product.

Bioaccumulative Potential – Ingredients No information available for this product.

Mobility in Soil

No information available for this product.

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of in accordance with local, state, and federal regulations.

Additional Information: Empty containers should be taken for local recycling, recovery or waste disposal.

SECTION 14: TRANSPORT INFORMATION					
In Accordance with DOT					
Proper Shipping Name	: Bulk - Combustible Liquids,	N.O.S. (Asphalt cutback); UN			
	1999, PG 3, III				
In Accordance with IMDG					
Proper Shipping Name	: Tars, liquid				
Hazard Class	: 3	In Accordance with IATA			
hoptifisation Alumbre	i 1989 liquid				
BackingChagup	i Al	In Accordance with TDG			
Mariersarikhangtonare	Not Regulated.				
PaskingChasup	<u>i</u> III				
Merina Calbut Mumber	i				
Packing Group	:				
Packing Group	:				

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 05/21/2025 Date of Issue: 08/17/2016 Version: 2.1

Marine Pollutant

SECTION 15: REGULATORY INFORMATION

:

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	CHINA	KECL	PICCS	AICS
Petroleum Asphalt	Х	Х	-	Х	-	-	Х	Х	Х	Х
Stoddard Solvent	Х	Х	Х	Х	Х	Х	Х	Х	Х	Х

TSCA	Complies
DSL	Complies
NDSL	Complies
EINECS	Complies
ELINCS	Complies
ENCS	Complies
CHINA	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

US Federal Regulations

Listed on the United States TSCA	(Toxic Substances Control Act) Inventory

Elastomeric Polymer (Proprietary)

Listed on the United States TSCA (Toxic Substances Control Act) Inventory

US State Regulations

California Proposition 65

This product contains no known Proposition 65 chemicals.

State Right-to-Know

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Petroleum Asphalt	Х	Х	Х		Х
Stoddard Solvent	Х	Х	Х		Х

Canadian Regulations

Ultra-Shield SB Waterproofing

All components are listed in the WHMIS DSL.			
WHMIS Classification	Not classified.		

2

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date

05/21/2025 2

```
Other Information
```

This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document GMX. Inc. 3014 Chamber Dr Monroe, NC 28110

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 05/21/2025 Date of Issue: 08/17/2016 Version: 2.1

North America GHS US 2016 & WHMIS