

# AIR GUARD® JOINT FABRIC



7 FLUID APPLIED | Membrane Waterproofing

RESIDENTIAL

## DESCRIPTION

Air Guard Joint Fabric is a strong, elastic polyester reinforcing fabric. It is a lightweight material ideal for use with cold-applied mastics. Air Guard Joint Fabric conforms easily and readily to irregular shapes and surfaces.

## ADVANTAGES

- Superior tensile strength and elongation
- Excellent elongation to break
- Will not unravel
- No fiber breakage
- Outstanding resistance to cold temperatures, cracking, rot, chemicals and solvents
- Unaffected by water immersion

## USES

Air Guard Joint Fabric is designed for use as the reinforcing fabric over the horizontal and vertical joints in plywood or OSB framing prior to the installation of the Air Guard VPA membrane system.

## APPLICATIONS

Air Guard Joint Fabric is the reinforcement layer in the Air Guard VPA membrane system. Typically is embedded in a base coating of Air Guard VPA, carefully brushed to ensure complete adhesion, and top dressed with an additional layer of Air Guard VPA membrane.

## TEMPERATURE RESISTANCE

Air Guard Joint Fabric can withstand temperatures up to 400°F (204°C) for short periods of time and temperatures up to 350°F (177°C) for indefinite periods.

## WEATHERING

Air Guard Joint Fabric is unaffected by UV radiation when covered with roof coatings or aggregate.

## FREIGHT CLASSIFICATION

Synthetic Fiber

## PACKAGING

Air Guard Joint Fabric is available in 6" and 4" x 300' rolls

## TECHNICAL SERVICES | PRODUCT SPECIFICATIONS

Type: Polymer modified asphalt waterproofing membrane

<b>Tensile Strength</b> (ASTM D 1682)	57.1 lbs. (25.9 kg)
<b>Elongation</b> (ASTM D 1682)	61.65%
<b>Tear Strength</b>	16.1 lbs. (7.30 kg)
<b>Mullen Burst</b> (ASTM D 3786)	176 lbs. (80.2 kg)

## May help to contribute to LEED® credits:

<b>EA Credit 1:</b>	Optimize Energy Performance
<b>EQ Credit 3.1:</b>	Construction IAQ Management Plan: During Construction
<b>EQ Credit 4.2:</b>	Low Emitting Materials: Paints and Coatings
<b>MR Credit 5.1:</b>	Regional Materials: 10% Extracted, Processed and Manufactured Regionally
<b>MR Credit 5.2:</b>	Regional Materials: 20% Extracted, Processed and Manufactured Regionally



**GMX, Inc.**  
3014 Chamber Dr.  
Monroe, NC 28110  
Toll Free: 866-228-7743  
[www.gmxwaterproofing.com](http://www.gmxwaterproofing.com)

LEED® Buildings and Leadership in Energy and Environmental Design® are trademarks of the U.S. Green Building Council. The Leadership in Energy and Environmental Design (LEED) Green Building Rating System is a voluntary, consensus-building national standard that was initiated by the U.S. Green Building Council (USGBC) for developing high-performance sustainable buildings.

030422