

## PRODUCT DESCRIPTION

BoneDry™ RG is a commercial grade waterproofing membrane designed to be applied with a roller. BoneDry RG is used as a below-grade exterior waterproofing compound and exhibits excellent strength, adhesion, and flexibility. BoneDry RG is a premium grade waterproofing compound used in commercial building construction and can be used for all other types of below-grade waterproofing.

BoneDry RG is designed to be applied with a roller. We recommend that the BoneDry RG be applied to a cured thickness of 40 - 60 mils. It may take several applications to obtain a 40 - 60 mil cured membrane. For detailed application instructions contact GMX at (866) 228-7743.

## APPLICATION

- Masonry foundations
- Poured foundations
- Pre-cast foundations
- Horizontal waterproofing
- Planters
- Retaining Walls
- Cavity wall air barrier

## TECHNICAL SERVICES | PRODUCT SPECIFICATIONS

Type: Polymer modified asphalt waterproofing membrane

<b>Color</b>	Black/ Brown
<b>Solids</b>	63% ± 2%
<b>Thickness</b>	40-60 mil dry
<b>Tensile Strength</b> ASTM D 412	87 psi
<b>Elongation</b> ASTM D 412	1800%
<b>MVT</b> ASTM E 96	0.19 gr/hr* sq. ft.
<b>Adhesion to Concrete</b> ASTM C 834	Exceeds
<b>Shore Hardness</b> ASTM C 836	75
<b>Crack Bridging</b> ASTM C 836	Exceeds
<b>Low Temp Flexibility</b> ASTM C 836	No Cracking
<b>Perm Rating</b> ASTM C 836	0.38 perms

**CAUTION:** KEEP FROM FREEZING DURING TRANSIT AND STORAGE.

## May help to contribute to LEED® credits:

<b>EA Credit 1:</b>	Optimize Energy Performance
<b>EQ Credit 3.1:</b>	Construction IAQ Management Plan: During Construction
<b>EQ Credit 4.2:</b>	Low Emitting Materials: Paints and Coatings
<b>MR Credit 5.1:</b>	Regional Materials: 10% Extracted, Processed and Manufactured Regionally
<b>MR Credit 5.2:</b>	Regional Materials: 20% Extracted, Processed and Manufactured Regionally



**GMX, Inc.**  
3014 Chamber Dr.  
Monroe, NC 28110  
Toll Free: 866-228-7743  
[www.gmxwaterproofing.com](http://www.gmxwaterproofing.com)

LEED® Buildings and Leadership in Energy and Environmental Design® are trademarks of the U.S. Green Building Council. The Leadership in Energy and Environmental Design (LEED) Green Building Rating System is a voluntary, consensus-building national standard that was initiated by the U.S. Green Building Council (USGBC) for developing high-performance sustainable buildings.