

Green Jacket +



7 SHEET APPLIED | Membrane Waterproofing

PRODUCT DESCRIPTION

Green Jacket PLUS is a water based all-polymer spray applied waterproofing emulsion. **Green Jacket PLUS** is solvent free; therefore it is fully compliant with VOC regulations in all 50 states. It provides seamless waterproofing protection for the most difficult jobs with tremendous elongation, strength and adhesion.

PRODUCT DESCRIPTION

- Will not delaminate from wall
- Solvent-free
- 100% rubber polymer emulsion

USES

Designed for use on parged / unparged masonry and concrete substrates. Do not backfill for 24 hours.

PREPARATION

All surfaces should be free from loose materials such as sand, dirt or other impediments and dry. Any cracks, spall, seams or joints should be flashed/caulked or patched. Only use when surface and air temperature is 35°F or greater during the application and for 12 hours after. Do Not apply if rain will fall with-in 12 hours after application.

APPLICATION

Green Jacket PLUS can be applied in multiple layers or as one coating. A 38 mil thick dry coating (70 mil wet) is recommended. **Green Jacket PLUS** should be used at a coverage rate of 22-24 sq.ft./ gallon. Apply using a roller, brush or spray device. **Green Jacket PLUS** does not have long-term stability to ultraviolet light, do not leave exposed to light more than 30 days. Please note, the application rate varies according to the porosity of the surface. Apply two coats for best results.

AVAILABILITY AND COST

GMX materials are produced in and shipped from our plant in Monroe, NC. For the name and number of the nearest GMX representative, call us at 866-228-7743.

WARRANTY

GMX may offer warranties up to 30 years or more for its membranes and system applications when they are installed by a Certified GMX installer in accordance with the published specifications in effect at the time of installation. For specific warranty terms and conditions, contact your local GMX representative or the Monroe, NC office.

TECHNICAL SERVICES

Your local GMX representative is available to assist you in selecting the appropriate product and to provide on site application assistance. For further information, please contact our Technical Service Department at 866-228-7743.

TECHNICAL SERVICES | PRODUCT SPECIFICATIONS

Type: Green Jacket PLUS

Color	Green
Solids	59-61%
Elongation (ASTM D-412)	2394%
Tensile Strength (ASTM D-412)	575 psi
Adhesion to Concrete (ASTM C-836)	Exceeds
Crack Bridging (ASTM C-836)	Exceeds
Low Temp Flexibility (ASTM C-836)	No Cracking
Hydrostatic Head (ASTM C-1306)	40 psi
Water Vapor Permeance (ASTM E-96) Wet	Less than 0.9 perms
UV Stability	none

CAUTION: Green Jacket PLUS is a water-based material. KEEP FROM FREEZING DURING TRANSIT AND STORAGE

May help to contribute to LEED® credits:

EA Credit 1:	Optimize Energy Performance
EQ Credit 3.1:	Construction IAQ Management Plan: During Construction
EQ Credit 4.2:	Low Emitting Materials: Paints and Coatings
MR Credit 5.1:	Regional Materials: 10% Extracted, Processed and Manufactured Regionally
MR Credit 5.2:	Regional Materials: 20% Extracted, Processed and Manufactured Regionally

Green Jacket +



GMX, Inc.
3014 Chamber Dr.
Monroe, NC 28110
Toll Free: 866-228-7743
www.gmxco.com

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperatures, application methods, test methods, actual site conditions and curing conditions. Installation conditions and methods can impact product performance. Consult your local GMX Sales Representative for Questions.

PRIOR TO EACH USE OF ANY GMX PRODUCT, THE USER MUST ALWAYS READ AND FOLLOW THE WARNINGS & INSTRUCTIONS ON THE PRODUCT'S MOST CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET WHICH ARE AVAILABLE ONLINE AT WWW.GMXCO.COM OR BY CALLING GMX AT 866-228-7743. NOTHING CONTAINED IN ANY GMX MATERIALS RELIEVES THE USER OF THE OBLIGATION TO READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS FOR EACH GMX PRODUCT AS SET FORTH IN THE CURRENT PRODUCT DATA SHEET, PRODUCT LABEL AND SAFETY DATA SHEET PRIOR TO PRODUCT USE.